












→ Especificação de Container

Equipment	Interior Dimensions	Door Opening	Top Opening	Tare Weight	Cubic Capacity	Payload (max weight)
20' dry container (standart) 	L 5,919mm W 2,340mm H 2,380mm	W 2,286mm H 2,278mm	-	1,900 kg 4,189 lbs	33,0 m <sup>3</sup> 1,165 cu. ft	22,100 kg 48,721 lbs
40' dry container (standart) 	L 12,045mm W 2,309mm H 2,379mm	W 2,280mm H 2,278mm	-	3,084 kg 6,799 lbs	67,3 m <sup>3</sup> 2,377 cu. ft	22,396 kg 60,397 lbs
40' high cube dry container 	L 12,056mm W 2,347mm H 2,284mm	W 2,340mm H 2,585mm	-	2,900 kg 6,393 lbs	76,0 m <sup>3</sup> 2,684 cu. ft	29,600 kg 65,256 lbs
20' reefer container 	L 5,428mm W 2,226mm H 2,240mm	W 2,286mm H 2,188mm	-	2,940 kg 6,482 lbs	27,5 m <sup>3</sup> 971 cu. ft	24,060 kg 53,043 lbs
40' reefer container 	L 11,207mm W 2,246mm H 2,183mm	W 2,216mm H 2,118mm	-	4,840 kg 10,670 lbs	54,9 m <sup>3</sup> 1,939 cu. ft	25,640 kg 56,526 lbs
40' high cube reefer container 	L 11,628mm W 2,294mm H 2,509mm	W 2,290mm H 2,535mm	-	4,430 kg 9,766 lbs	66,9 m <sup>3</sup> 2,363 cu. ft	28,070 kg 61,883 lbs
20' open top container 	L 5,919mm W 2,340mm H 2,286mm	W 2,286mm H 2,251mm	L 5,425mm W 2,222mm	2,174 kg 4,793 lbs	31,6 m <sup>3</sup> 1,116 cu. ft	21,826 kg 48,117 lbs
40' open top container 	L 12,043mm W 2,340mm H 2,272mm	W 2,279mm H 2,278mm	L 11,585mm W 2,162mm	4,300 kg 9,480 lbs	64,0 m <sup>3</sup> 2,260 cu. ft	26,181 kg 57,720 lbs
20' flat rack container 	L 5,662mm W 2,438mm H 2,327mm	-	-	2,530 kg 5,578 lbs	-	21,470 kg 47,333 lbs
20' collapsible flat rack container 	L 5,946mm W 2,126mm H 2,233mm	-	-	2,900 kg 6,393 lbs	-	27,100 kg 59,745 lbs
40' flat rack container 	L 12,080mm W 2,438mm H 2,103mm	-	-	5,480 kg 12,081 lbs	-	25,000 kg 55,115 lbs

L = Length (Comprimento) W = Width (Largura) H = Height (Altura)